



16A model	H12C13-16A-WCR_OE/3B-1	16A MCB x 1	3M Cordset 3W 1.5mm sq. H05V V-F	Open end 16A
-----------	------------------------	-------------	--	-----------------

Circuit : output 16A max., C13 # 1 - 12

**Specification**

Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity	: 8 to 95% RH, non-condensing
Chassis Material / Color	: Steel / Black
Product Dimension	: 442W x 300D x 44H (mm)
Packing Dimension	: 540W x 540D x 105H (mm)
Net / Gross Weight	: 3.2 kg / 3.7 kg

**Meter Features**

Local Display	: Field replaceable 2" color LCD with touchscreen
Bank Measurement	: Current ( A ), Energy ( kWh ), Voltage ( V ) & Power factor
Accuracy	: ±1% Billing-grade
IP Access	: via IP dongle, one IP Access up to 32 PDU Levels
Cascade	: Up to 32 PDU under single IP address via IP dongle
SNMP	: V2 / V3 via IP dongle
Sensor Port x 2	: Temp. Sensor / Temp. + Humid. Sensor

**IP dongle ( option )**

- Dual LAN Network Failover
- 10/100 Ethernet & Gigabit Ethernet standard
- Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol

**EMC Certificates**

CE / EMC	: EN55032:2015/A11:2020
	: EN IEC 61000-3-2:2019/A1:2021
	: EN61000-3-3:2013/A2:2021
	: EN55035:2017/A11:2020

**Safety Certificates**

CE / LVD	: EN 62368-1:2014, EN 62368-1:2014/A11:2017
CB	: IEC 62368-1:2014
UKCA	: BS EN 62368-1:2014+A11: 2017

**Environment** : RoHS, Reach & WEEE